

 BHW Floors

 (800) 607-2414
 TEL

 (206) 264-9365
 FAX

 info@bhwfloors.com
 Email

## **SAWATCH** FLOORING SPECIFICATIONS

			R (2. 6) A Martin Constant of the second
PRODUCT INFORMATION			
CONSTRUCTION	Engineered Rigid Core Stone-Polymer Composite (SPC) / 2	1 11 321311 13	
PLANK DIMENSIONS	4mm + 1.5mm EVA Attached Pad Thickness x 7-7/32" Width x 48-1/32" Length		A A A A A A A A A A A A A A A A A A A
MILLING	4 sided Micro-Bevel Edge / Uniclic® Locking System		Children and the second
FINISH	Aluminer <sup>™</sup> UV Cured Acrylic / 10% Sheen / Textured		CIMARRON 55643
COLOR VARIANCE	Low		
INSTALLATION	Float or Glue. Radiant floor heating compatible. Above, on, or below grade.		
ENVIRONMENTAL	FloorScore® Certified / 100% Virgin PVC		
WATER PERFORMANCE	100% waterproof and safe to install in full bathrooms, laur	ndry rooms, and mudrooms.	
PACKAGING			KEYSTONE 55647
BOX WEIGHT: 52 LBS	SQFT PER BOX: 28.84 BOX DIMENSIONS: 3" x 8" x 49"		
PLANKS PER BOX: 12	PACK SIZE: 40 Boxes/Pallet PALLET DIMENSIONS: 30" x 42" x 50"		
VARRANTY			SOMERSET 55649
FINISH	50-year Residential / 15-year Light Commercial		
STRUCTURE	Lifetime Structural Warranty		Marine Marine Marine
			A STANDAR CAN
RESOURCES			
	ns of our installation and maintenance guides, as well as watch	h installation videos, at	SILVERTHORNE 55651
	/ ALUMINER <sup>™</sup>	MIRA MAR 55665	JUNIPERO 55660
	(2 LAYERS OF PROTECTIVE COATING	G)	
	20MIL (0.5MM)		
	WEAR LAYER	EUCLID 55667	OBISPO 55661
	HIGH RESOLUTION	ON CON	
	DECOR FILM	CENTRON INCLUSION	I MANUTAS EN MAL
		MOUNO FECCO	LOMA EECCO
	RIGID CORE SPO	MOLINO 55668	LOMA 55662
			MARTIN STRUCTURE
	1.5MM EVA PAD		
			BELMONT 55663
	and the second se		
	tloor	a series of the	
02/15/2024			TERMINO 55664

CO SCS Global Services

